

Model

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 27°C bottle, 27°C ambient

! At 32°C bottle, 32°C ambient

! At 38°C bottle, 38°C ambient

Performance (litres of hot water / hour)

Refrigerant type

Refrigerant charge

Cold tank capacity

Hot tank capacity

Power consumption

POU1CCTHSY

13,0 kg

45,5 cm x 31 cm x 36 cm

4.6 litres per hour

3.0 litres per hour

2.1 litres per hour

1.5 litres per hour

7.9

R134a

35 g

2.2 litres

1.5 litres

545 Watt

Model

Weight

Dimensions (H x W x D)

Performance (litres of cold water / hour)

! At 21°C bottle, 21°C ambient

! At 27°C bottle, 27°C ambient

! At 32°C bottle, 32°C ambient

! At 38°C bottle, 38°C ambient

Refrigerant type

Refrigerant charge

Cold tank capacity

Power consumption

POU1CCTKY

12,0 kg

45,5 cm x 31 cm x 36 cm

4.6 litres per hour

3.0 litres per hour

2.1 litres per hour

1.5 litres per hour

R134a

35 g

2.2 litres

95 Watt

